

Calling APIs

This was an example of a call requested from the LSIO discord to add a tag on completion of a torrent. This is a working example of authenticating to the API and then calling it to add the "done" tag.

```
curl -i -XPOST http://localhost:8080/api/v2/torrents/addTags \  
--data 'hashes=%l&tags=done' \  
--cookie \  
$(curl -i \  
--header 'Referer: http://localhost:8080' \  
--data 'username=admin&password=<YOURPASSWORDHERE>' \  
http://localhost:8080/api/v2/auth/login | grep set-cookie | tr ";" " " | awk '{print $2}')
```

<https://github.com/qbittorrent/qBittorrent/wiki/External-programs:-How-to>

[https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#authentication](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#authentication)

[https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-\(qBittorrent-4.1\)#add-torrent-tags](https://github.com/qbittorrent/qBittorrent/wiki/WebUI-API-(qBittorrent-4.1)#add-torrent-tags)

Revision #2

Created 29 July 2020 23:33:04 by Tokugero

Updated 29 July 2020 23:40:23 by Tokugero